



- Precision made of superior quality thermal shock resisting hotwork die steel
- Hot-forged heads provide uniform grain flow, higher tensile strength
- Outside diameter nitrided to 65-74 HRc hardness and finished to minimize wear
- Heads annealed for easy machining
- Centerless ground and polished outer diameter

### 1/4" Diameter Series

ITEM NUMBER	G PIN DIA	H HEAD DIA	K HEAD THICK	M PIN LENGTH
7110	+.000 .250 -.001	7/16	3/16	3-7/16
7111				3-15/16
7112				4-7/16
7113				4-15/16
7114				5-7/16
7115				5-15/16
7116				6-7/16

For longer lengths, use EX 17 Ejector Pins (page 3).

### 3/8" Diameter Series

ITEM NUMBER	G PIN DIA	H HEAD DIA	K HEAD THICK	M PIN LENGTH
7210	+.000 .375 -.001	5/8	1/4	3-7/8
7211				4-3/8
7212				4-7/8
7213				5-3/8
7214				5-7/8
7215				6-3/8
7216				6-7/8
7217				7-3/8
7218				7-7/8
7219				8-3/8
7220				8-7/8
7221				9-3/8

For longer lengths, use EX 25 Ejector Pins (page 3).

#### Quantity Discounts

300 to 599 . . . . . Less 5%

600 or more . . . . . Less 10%

Discounts apply to Ejector Pins, Core Pins, Return Pins and Sprue Puller Pins. Standard sizes may be combined on one order for quantity discounts.

#### When ordering please specify:

- Item Number and Quantity
- Method of Shipment

**Specials Available.**  
**See "D-M-E Special Pins & Sleeves"**