

## REFERENCE CHART

DESCRIPTION	TOLERANCE FROM NOMINAL	SURFACE HARDNESS Rc	CORE HARDNESS Rc
<b>P &amp; SP</b> HARDENED THROUGHOUT EJECTOR PIN 1/32" THRU 1/2"	-0.0005 -0.0008	65 - 70	50 - 52
<b>P</b> HARDENED THROUGHOUT EJECTOR PIN 17/32" THRU 1"	-0.0005 -0.0010	65 - 70	50 - 52
<b>NP</b> NITRIDED EJECTOR PIN	+0.000 -0.001	65 - 74	35 - 40
<b>CPH</b> HARD CORE PIN	+0.0010 +0.0005	50 - 55	50 - 55
<b>CPS</b> SOFT CORE PIN	+0.0010 +0.0005	30 - 35	30 - 35
<b>SL</b> NITRIDED SLEEVE	O.D. +0.000 -0.001 I.D. +0.0005 -0.0000	65 - 74	30 - 35
<b>BE</b> EJECTOR BLADE	BLADE THICK. +0.0000 AND WIDTH -0.0003	50 - 52	50 - 52
<b>AR</b> STRAIGHT ARMOR PIN	1/8-1/2 = -0.0005 -0.0008 5/8-3/4 = -0.0005 -0.0010	70 - 72	50 - 52
<b>ARS</b> STEP ARMOR PIN	-0.0005 -0.0008	70 - 72	50 - 52
<b>CPM</b> moldMAX® PIN	+0.000 -0.001	36 - 42	36 - 42
<b>RP</b> NITRIDED RETURN PIN	+0.000 -0.001	65 - 74	35 - 40
<b>A</b> NITRIDED ANGLE PIN	-0.0010 -0.0015	65 - 74	35 - 40

### PRICING

ALL ITEMS ARE BILLED AT PRICES IN EFFECT ON THE DATE OF SHIPMENT. PRICES ARE SUBJECT TO CHANGE WITHOUT NOTICE.

### TERMS

NET 30 DAYS

### TRANSPORTATION

ALL SHIPMENTS ARE MADE F.O.B. SHIPPING POINT.

### CLAIMS

CLAIMS FOR ANY ERRORS, SHORTAGES, OR DEFECTS MUST BE MADE WITHIN TEN (10) DAYS FROM RECEIPT OF SHIPMENT.

ALL ITEMS CLAIMED DEFECTIVE MUST BE INSPECTED BY PCS PRIOR TO REPLACEMENT OR CREDIT.

### RETURNS

APPROVAL MUST BE OBTAINED FROM PCS, PRIOR TO RETURNING ANY MERCHANDISE. SPECIAL ORDERS I.E., SPECIAL SLEEVES, PINS AND WEAR PLATES ARE NOT SUBJECT TO RETURN.

SEE Tab for Section K for Complete Terms & Conditions

